

15W LED A65 LED BULB DIMMABLE E26

Item # 705 | L15WA21DIM/30K / Item # 706 | L15WA21DIM/50K

Introducing 15W Dimmable Wet Location approved LED Lamp designed with further improvements to withstand harsh poultry environment



15W-A21-WET LOCATION DIMMABLE BULB

- 1** > UL-V0(f1) Flame retardant, UV and impact resistant flame retardant PC Diffuser
- > 120-130 Degree Directional Lighting ensures full utilization of Light on floor

Special Joint with Silicone Sealing all around to prevent moisture, dust to penetrate the lamp **2**

- 3** High quality Bridgelux LED used offering long life under harsh conditions

Bigger size flame retardant UL-V0 PBT heat sink moulded over high grade Aluminium for better heat dissipation and prevents corrosion. **4**

- 5** > Can sustain 2KV Surge
- > High quality and professional grade Electronic components with special dimming IC used to provide Flicker Free dimming up to 1% level

Nickel Plated Brass E26 Cap used having high corrosion resistance **6**

1 LAMP SPECIFICATION

➤ Lamp Type	A21- Wet Location Approved	➤ Wattage Comparison (FC on Floor)	150W GLS Lamp
➤ Dimmable (Y/N)	YES	➤ Rated Average Life (hours) L70	25,000
➤ Base	E26 base cap	➤ Reliable Operating Temperature	- 4F to 113F
➤ Lamp Finish/Type	A21 LED Bulb		
➤ Lamp Wattage	15W		

2 PHOTOMETRIC CHARACTERISTICS

➤ Initial Lumens	1450(3000K), 1600(5000K)		
➤ Centre Beam Candle Power (CBCP)Cd	340(3000K), 370(5000K)		
➤ Beam Angle (50% I Max) in Degree	130	➤ Color Temperature	3000K / 5000K
➤ Initial Lumens per Watt	97(3000K), 107(5000K)	➤ Color Rendering Index (CRI)	82

3 ELECTRICAL CHARACTERISTICS

➤ Input Line Voltage/Frequency	120V 60 Hz	➤ Power Factor	0.95
➤ Lamp rated Wattage	15W	➤ Input Line Current	140mA
➤ Total Harmonic Distortion	<20%	➤ Dimming Range in %	0-100%

4 DIMENSIONAL CHARACTERISTICS

➤ Nominal Length (Inches/mm)	5.10" / 130 mm	➤ Diameter	2.56" / 65 mm
------------------------------	----------------	------------	---------------

5 PRODUCT INFORMATION

➤ Description	15W LED A21 LED Bulb Dimmable E26 - 3000K/5000K		
➤ Primary Application	Commercial, Agriculture.		
➤ Warranty	5 Years from date of purchase		
➤ TCLP Compliant	Yes	➤ RoHS Compliant	Yes
➤ Energy Star or LM79 (Y/N)	Yes (LM79)	➤ ETL - Wet Location	Yes UL1993/CSA22.2

6 PACKING DETAILS

➤ Color Box Size (Inches) 1x1	2.68 x 2.68 x 5.35	➤ Inner Carton Size (Inches) 1x12	11.1 x 8.4 x 5.8
➤ Master Carton Size (Inches) 1x48	17.8 x 11.8 x 12.7	➤ Gross Weight / Net Weight (lbs)	16 lb / 9 lb



WWW.SECREPRO.COM
 Ange-Gardien, QC
 1.888.446.4647



LOUIS BONNEVILLE
 President and sales manager
louis@secrepro.com